

# Disconnect and Fuse Terminals

## Screw Type Fuse Terminals

Item no: **ASK 3 F**  
 Order no: **354 109**



Torque: 0,5 Nm

Electrical Ratings	
--------------------	--

Voltage/Current/Cross-Section	600 V ~ / 6.3 A / 4 mm <sup>2</sup>
UL	600 V ~ / 10 A / AWG 26-10
Insulation Stripping Length	12 mm

Connection Data	
-----------------	--

Solid Strand, Screw Connection	0,5 - 6 mm <sup>2</sup>
Fine Strand, Screw Connection	1,5 - 4 mm <sup>2</sup>
AWG Conductor	26 ..... 10

Ordering Data	Type	Cat. No.
---------------	------	----------

Polyamide 6.6	Grey	ASK 3 F	354 100 / 354 109
---------------	------	---------	-------------------

End Bracket			
-------------	--	--	--

Thickness 8 mm KD 3	MR 35 For Grey	KD 3	495 040 / 495 049
------------------------	----------------	------	-------------------



End Plate			
-----------	--	--	--

Thickness 1.5 mm NPP ASK 3	Polyamide 6.6	Grey	NPP ASK 3	450 059
-------------------------------	---------------	------	-----------	---------



Cross Connection		
------------------	--	--

	UK 4/10	476 239
--	---------	---------

