

Disconnect and Fuse Terminals

Screw Type Fuse Terminals

Item no: **ASK 3 FLD**
Order no: --- --9



Torque: 0,5 Nm

Electrical Ratings	
Voltage/Current/Cross-Section	- V ~ / 6.3 A / 4 mm ²
UL	- V ~ / 10 A / AWG 26-10
Insulation Stripping Length	12 mm

Connection Data	
Solid Strand, Screw Connection	0,5 - 6 mm ²
Fine Strand, Screw Connection	1,5 - 4 mm ²
AWG Conductor	26 10

Ordering Data		Type	Cat. No.
Polyamide 6.6	Grey	ASK 3 FLD	354 210 / 354 219 (24V AC)
		ASK 3 FLD	354 220 / 354 229 (24V DC)
		ASK 3 FLD	354 310 / 354 319 (48V AC)
		ASK 3 FLD	354 320 / 354 329 (48V DC)
		ASK 3 FLD	354 510 / 354 519 (110V AC)
		ASK 3 FLD	354 520 / 354 529 (110V DC)
		ASK 3 FLD	354 610 / 354 619 (220V AC)
		ASK 3 FLD	354 620 / 354 629 (220V DC)

End Bracket			
Thickness 8 mm	MR 35 For Grey	KD 3	495 040 / 495 049
KD 3			



End Plate				
Thickness 1.5 mm	Polyamide 6.6	Grey	NPP ASK 3	450 059
NPP ASK 3				



Cross Connection		
	UK 4/10	476 239

