

Disconnect and Fuse Terminals

Fuse Terminals for American Standards

Item no: **ASK 4 LD**
Order no: --- --9



Torque: 0,8 Nm

Electrical Ratings			
Voltage/Current/Cross-Section		- V ~ / - A / 6 mm ²	
UL		- V ~ / - A / AWG 22-8	
Insulation Stripping Length		12 mm	
Connection Data			
Solid Strand, Screw Connection		0,5 - 10 mm ²	
Fine Strand, Screw Connection		1,5 - 6 mm ²	
AWG Conductor		22 8	
Ordering Data		Type	Cat. No.
Polyamide 6.6	Grey	ASK 4 LD	351 710 / 351 719 (24V AC)
		ASK 4 LD	351 720 / 351 729 (24V DC)
		ASK 4 LD	351 730 / 351 739 (48V AC)
		ASK 4 LD	351 740 / 351 749 (48V DC)
		ASK 4 LD	351 750 / 351 759 (110V AC)
		ASK 4 LD	351 760 / 351 769 (110V DC)
		ASK 4 LD	351 770 / 351 779 (220V AC)
		ASK 4 LD	351 780 / 351 789 (220V DC)
End Bracket			
Thickness 8 mm	MR 35 For Grey	KD 3	495 040 / 495 049
KD 3			

