

# Multi Layer Screw Clamp Terminals

## Screw Type Terminal Blocks For Initiators, Actuators And Motors

Item no: **PUK 3**  
Order no: **324 109**



Torque:0,4 Nm

Electrical Ratings	
--------------------	--

Voltage/Current/Cross-Section	500 V ~ / 24 A / 2.5 mm <sup>2</sup>
VDE (IEC 60947-7-1)	440 V ~ / 24 A / 2.5 mm <sup>2</sup>
UL	300 V ~ / 24 A / 24...12 AWG
Insulation Stripping Length	9 mm

Connection Data	
-----------------	--

Solid Strand, Screw Connection	0,5 - 4 mm <sup>2</sup>
Fine Strand, Screw Connection	1,5 - 2,5 mm <sup>2</sup>
AWG Conductor	26 ..... 12

Ordering Data	Cat. No.
---------------	----------

Polyamide 6.6	Grey 324 109
---------------	--------------

End Bracket	Type	Cat. No.
-------------	------	----------

Thickness 8 mm KD 3	MR 35 For Grey	KD 3 495 040 / 495 049
------------------------	----------------	---------------------------



End Plate - Partition	
-----------------------	--

Thickness 1,5 mm NPP PUK 3	Polyamide 6.6	Grey NPP PUK 3 450 139
-------------------------------	---------------	---------------------------



Cross Connection	
------------------	--

	UK 2.5/10 480 139
--	----------------------

