

# Disconnect and Fuse Terminals

## Spring Clamp Fuse and Disconnect Terminals

Item no: **YBK IB**  
Order no: **363 209**



Electrical Ratings	
--------------------	--

Voltage/Current/Cross-Section	500 V ~ / 10 A / 4 mm <sup>2</sup>
UL	600 V ~ / 10 A / AWG 22-10
Insulation Stripping Length	12 mm

Connection Data	
-----------------	--

Solid Strand, Screw Connection	0,5 - 4 mm <sup>2</sup>
Fine Strand, Screw Connection	0,5 - 4 mm <sup>2</sup>
AWG Conductor	22 ..... 10

Ordering Data		Type	Cat. No.
---------------	--	------	----------

Polyamide 6.6	Grey	YBK IB	363 200 / 363 209
---------------	------	--------	-------------------

End Bracket			
-------------	--	--	--

Thickness 8 mm KD 4	MR 35 For Grey	KD 4	495 059
------------------------	----------------	------	---------



End Plate			
-----------	--	--	--

Thickness 1,5 mm NPP YBK S - YBK I	Polyamide 6.6	Grey	NPP YBK S - YBK I	450 069
---------------------------------------	---------------	------	-------------------	---------



Cross Connection	
------------------	--

	UK 6/10	476 249
--	---------	---------

