

Disconnect and Fuse Terminals

Spring Clamp Fuse and Disconnect Terminals

Item no: **YBK ILD**
Order no: --- --9



Electrical Ratings	
Voltage/Current/Cross-Section	- V ~ / - A / 4 mm ²
UL	- V ~ / - A / AWG 22-10
Insulation Stripping Length	12 mm

Connection Data	
Solid Strand, Screw Connection	0,5 - 4 mm ²
Fine Strand, Screw Connection	0,5 - 4 mm ²
AWG Conductor	22 10

Ordering Data		Type	Cat. No.
Polyamide 6.6	Grey	YBK ILD	355 810 / 355 819 (24V AC)
		YBK ILD	355 820 / 355 829 (24V DC)
		YBK ILD	355 830 / 355 839 (48V AC)
		YBK ILD	355 840 / 355 849 (48V DC)
		YBK ILD	355 850 / 355 859 (110V AC)
		YBK ILD	355 860 / 355 869 (110V DC)
		YBK ILD	355 870 / 355 879 (220V AC)
		YBK ILD	355 880 / 355 889 (220V DC)

End Bracket			
Thickness 8 mm	MR 35 For Grey	KD 4	495 059
KD 4			



End Plate			
Thickness 1,5 mm	Polyamide 6.6	Grey	NPP YBK S - YBK I 450 069
NPP YBK S - YBK I			



Cross Connection	
	UK 6/10 476 249

