

# Disconnect and Fuse Terminals

## Spring Clamp Fuse and Disconnect Terminals

Item no: **YBK SB**  
Order no: **363 109**



### Electrical Ratings

|                               |                                    |
|-------------------------------|------------------------------------|
| Voltage/Current/Cross-Section | 500 V ~ / 10 A / 4 mm <sup>2</sup> |
| UL                            | 600 V ~ / 10 A / AWG 22-10         |
| Insulation Stripping Length   | 12 mm                              |

### Connection Data

|                                |                         |
|--------------------------------|-------------------------|
| Solid Strand, Screw Connection | 0,5 - 4 mm <sup>2</sup> |
| Fine Strand, Screw Connection  | 0,5 - 4 mm <sup>2</sup> |
| AWG Conductor                  | 22 ..... 10             |

### Ordering Data

|               |      | Type   | Cat. No.          |
|---------------|------|--------|-------------------|
| Polyamide 6.6 | Grey | YBK SB | 363 100 / 363 109 |

### End Bracket

|                |                |      |         |
|----------------|----------------|------|---------|
| Thickness 8 mm | MR 35 For Grey | KD 4 | 495 059 |
| KD 4           |                |      |         |



### End Plate

|                   |               |      |                   |         |
|-------------------|---------------|------|-------------------|---------|
| Thickness 1,5 mm  | Polyamide 6.6 | Grey | NPP YBK S - YBK I | 450 069 |
| NPP YBK S - YBK I |               |      |                   |         |



### Cross Connection

|  |  |         |         |
|--|--|---------|---------|
|  |  | UK 6/10 | 476 249 |
|--|--|---------|---------|

