

# Disconnect and Fuse Terminals

## Spring Clamp Fuse and Disconnect Terminals

Item no: **YBK SLD**

Order no: --- --9



Electrical Ratings	
Voltage/Current/Cross-Section	- V ~ / - A / 4 mm <sup>2</sup>
UL	- V ~ / - A / AWG 22-10
Insulation Stripping Length	12 mm

Connection Data	
Solid Strand, Screw Connection	0,5 - 4 mm <sup>2</sup>
Fine Strand, Screw Connection	0,5 - 4 mm <sup>2</sup>
AWG Conductor	22 ..... 10

Ordering Data		Type	Cat. No.
Polyamide 6.6	Grey	YBK SLD	355 710 / 355 719 (24V AC)
		YBK SLD	355 720 / 355 729 (24V DC)
		YBK SLD	355 730 / 355 739 (48V AC)
		YBK SLD	355 740 / 355 749 (48V DC)
		YBK SLD	355 750 / 355 759 (110V AC)
		YBK SLD	355 760 / 355 769 (110V DC)
		YBK SLD	355 770 / 355 779 (220V AC)
		YBK SLD	355 780 / 355 789 (220V DC)

End Bracket			
Thickness 8 mm	MR 35 For Grey	KD 4	495 059
KD 4			



End Plate			
Thickness 1,5 mm	Polyamide 6.6	Grey	NPP YBK S - YBK I 450 069
NPP YBK S - YBK I			



Cross Connection	
	UK 6/10 476 249

