



**DRIP-PROOF • C FACE LESS BASE • THREE PHASE**

HP	RPM 60 Hz	NEMA Frame	Catalog Number	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
1/6	1725	...	...	...	...	...	...	...
1/4	1725	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...
1/3	1725	...	...	...	...	...	...	...
	1725	S56C	<b>100048</b>	17	208-230/460	1.6	64.3	9.49
	1725	...	...	...	...	...	...	...
1/2	1725	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...
	1725	S56C	<b>100049</b>	21	208-230/460	2.0	68.0	9.99
	1725	...	...	...	...	...	...	...
3/4	1725	S56C	<b>100050</b>	24	208-230/460	2.8	75.0	10.49
1	1725	56C	<b>110043</b>	22	208-230/460	4.2	78.5	10.38
	1725	143TC	<b>120172</b>	26	208-230/460	4.2	78.5	11.28
1½	1725	56C	<b>110044</b>	27	208-230/460	5.6	78.5	10.88
	1725	145TC	<b>120081</b>	34	208-230/460	5.6	78.5	11.78
2	1725	56C	<b>115553</b>	32	208-230/460	6.2	78.5	11.19
	1725	145TC	<b>120035</b>	33	208-230/460	6.2	78.5	11.19
3	1725	...	...	...	...	...	...	...
	1725	145TC	<b>121405</b>	45	208-230/460	8.6	82.5	13.12
	1740	182TC	<b>131489</b>	65	230/460	8.0	80.0	11.69
5	1725	184TC	<b>131490</b>	55	208-230/460	14.2	84.0	12.69
7½	1740	184TC	<b>131739</b>	108	230/460	20.0	87.0	14.70
	1740	...	...	...	...	...	...	...
	1750	S213TC	<b>131527</b>	88	230/460	20.0	87.0	15.69
	1760	213TC	<b>140580</b>	115	208-230/460	20.0	88.5	15.25
10	1740	215TC	<b>140108†</b>	132	208-230/460	28.0	89.5	16.75
	1750	...	...	...	...	...	...	...
15	1760	...	...	...	...	...	...	
20	1760	...	...	...	...	...	...	

**TEFC • C FACE LESS BASE • THREE PHASE**

NEMA Frame	Catalog Number	App. Wgt. (lbs.)	Voltage	FL Amps 230V	% FL Eff.	"C" Dim. (Inches)
48CZ➤	<b>102662</b>	15	208-230/460	1.3	66.0	9.03
48CZ➤	<b>101966●</b>	18	208-230/460	1.2	65.0	9.03
48CZ➤	<b>101981</b>	17	208-230/460	1.6	66.0	9.44
S56C	<b>101648●</b>	17	208-230/460	1.9	78.0	9.56
S56C	<b>101767</b>	19	208-230/460	1.4	58.0	9.69
48CZ➤	<b>102664</b>	20	208-230/460	1.6	64.3	10.31
S56C	<b>101769</b>	20	208-230/460	1.6	64.8	9.69
56C	<b>110045●</b>	19	208-230/460	1.3	72.0	9.94
48CZ➤	<b>100486●</b>	24	208-230/460	1.9	75.0	11.02
48CZ➤	<b>102666</b>	24	208-230/460	1.9	75.0	11.06
56C	<b>110046●</b>	23	208-230/460	1.8	78.5	10.44
56C	<b>110458</b>	19	208-230/460	2.0	74.0	10.81
56C	<b>110047</b>	22	208-230/460	2.8	77.0	10.81
56C	<b>110048</b>	24	208-230/460	3.8	77.0	11.31
143TC	<b>120024</b>	26	208-230/460	3.8	77.0	11.75
56C	<b>110125</b>	29	208-230/460	5.0	78.5	11.81
145TC	<b>120037</b>	32	208-230/460	5.0	80.0	12.75
56C	<b>110451</b>	34	208-230/460	6.2	81.5	12.81
145TC	<b>120038</b>	35	208-230/460	6.2	81.5	12.75
56C	<b>113890♣</b>	43	208-230/460	8.6	82.5	13.81
145TC	<b>121035♣</b>	44	230/460	8.6	82.5	14.25
182TC	<b>131491</b>	52	230/460	9.0	82.5	13.97
184TC	<b>131492</b>	64	230/460	13.2	82.5	14.48
184TC	<b>131606</b>	66	208-230/460	19.6	87.0	16.47
213TC	<b>151346</b>	162	208-230/460	18.4	87.9	18.61
S213TC	<b>131528</b>	102	230/460	9.8	87.0	16.96
.....	...	...	...	...	...	...
215TC	<b>140109†</b>	141	208-230/460	26.0	89.5	18.71
215TC	<b>151348</b>	185	208-230/460	24.6	88.4	16.61
254TC	<b>151350</b>	284	208-230/460	37.0	90.0	23.80
256TC	<b>151352</b>	367	208-230/460	48.0	91.2	25.50

➤ Shaft extension has keyway and flat 180° apart for ease of mounting. Useable shaft is 1½" long by 1/2" diameter, 1/8" keyway.  
● These motors are totally enclosed, non-ventilated — Others are fan cooled.  
† Class F insulated.  
♣ These totally enclosed three phase motors have 1.0 service factors.

**SHADED FRAME INDICATES CAST IRON CONSTRUCTION**