



C FACE MOTORS • SINGLE PHASE

LESS BASE • CAPACITOR START • GENERAL PURPOSE



DRIP-PROOF • C FACE LESS BASE • SINGLE PHASE

| HP | RPM 60 Hz | NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | Over- load Prot. | F.L. Amps 230V | "C" Dim. (Inches) | |
|------|-----------------|---------------|-------------------|---------------|---------------|------------------------|-------------|------------------------|----------------------|-------------------------|-------|
| 1/6 | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 1/4 | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1725 | S56C | 100023 | \$186 | A | 17 | 115/208-230 | None | 2.7 | 9.24 | |
| | 1725 | S56C | 101521 | 201 | A | 17 | 115/208-230 | Auto. | 2.7 | 9.24 | |
| 1/3 | 3450 | S56C | 100354 | 163 | A | 17 | 115/208-230 | None | 2.8 | 8.99 | |
| | 3450 | S56C | 100355 | 171 | A | 17 | 115/208-230 | Auto. | 2.8 | 8.99 | |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1725 | S56C | 100024 | 215 | A | 17 | 115/208-230 | None | 3.3 | 9.24 | |
| | 1725 | S56C | 100018 | 232 | A | 18 | 115/208-230 | Man. | 3.3 | 9.24 | |
| | 1725 | S56C | 101522 | 228 | A | 17 | 115/208-230 | Auto. | 3.3 | 9.24 | |
| 1/2 | 3450 | S56C | 100356 | 171 | A | 19 | 115/208-230 | None | 3.4 | 9.99 | |
| | 3450 | S56C | 100054 | 185 | A | 18 | 115/208-230 | Auto. | 3.4 | 9.99 | |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1725 | S56C | 100025 | 244 | A | 19 | 115/208-230 | None | 4.4 | 9.99 | |
| | 1725 | S56C | 100019 | 262 | A | 21 | 115/208-230 | Man. | 4.4 | 9.99 | |
| | 1725 | S56C | 100020 | 259 | A | 20 | 115/208-230 | Auto. | 4.4 | 9.99 | |
| | 1140 | S6C | 110381 | 444 | A | 32 | 115/208-230 | None | 5.0 | 11.38 | |
| | 3/4 | 3450 | S56C | 100357 | 221 | A | 24 | 115/208-230 | None | 4.9 | 10.49 |
| | | 3450 | S56C | 100055 | 242 | A | 24 | 115/208-230 | Auto. | 4.9 | 10.49 |
| | | 1725 | S56C | 100026 | 295 | A | 24 | 115/208-230 | None | 5.4 | 10.99 |
| 1725 | | S56C | 100021 | 319 | A | 24 | 115/208-230 | Man. | 5.4 | 10.99 | |
| 1725 | | S56C | 101523 | 314 | A | 26 | 115/208-230 | Auto. | 5.4 | 10.99 | |
| 1140 | | S6C | 110382 | 495 | A | 46 | 115/208-230 | None | 6.4 | 12.88 | |
| 1 | 3450 | S6C | 110384 | 235 | A | 28 | 115/208-230 | None | 6.0 | 10.88 | |
| | 3450 | S6C | 113337 | 262 | A | 28 | 115/208-230 | Auto. | 6.0 | 10.88 | |
| | 1725 | S6C | 110220 | 313 | A | 30 | 115/208-230 | None | 6.4 | 10.88 | |
| | 1725 | S6C | 110036 | 331 | A | 27 | 115/208-230 | Man. | 6.4 | 10.88 | |
| | 1725 | 143TC | 121002 | 340 | B | 31 | 115/208-230 | None | 6.4 | 11.28 | |
| | 1 1/2 | 3450 | S6C | 110387 | 324 | A | 28 | 115/208-230 | None | 8.6 | 10.88 |
| 3450 | | S6C | 113336 | 344 | A | 28 | 115/208-230 | Auto. | 8.6 | 10.88 | |
| 3450 | | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 1725 | | S6C | 110388☆ | 379 | A | 38 | 115/208-230 | None | 8.6 | 11.84 | |
| 1725 | | S6C | 110037☆ | 396 | A | 39 | 115/208-230 | Man. | 8.6 | 11.84 | |
| 1725 | | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 2 | | 3450 | S6C | 110390 | 426 | A | 37 | 115/208-230 | None | 12.0 | 11.88 |
| | 3450 | S6C | 113335 | 444 | A | 36 | 115/208-230 | Auto. | 12.0 | 11.88 | |
| | 3450 | 145TC | 121184 | 433 | B | 37 | 115/208-230 | None | 12.0 | 12.28 | |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1725 | 145TC | 120073☆ | 430 | B | 49 | 115/208-230 | None | 10.5 | 13.28 | |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 3 | 3450 | S6C | 113334 | 452 | A | 36 | 230 | Auto. | 15.0 | 11.88 | |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1740 | 184TC | 131544 | 491 | B | 73 | 115/208-230 | None | 16.9 | 14.19 | |
| 5 | 3450 | 184TC | 131777☆ | 657 | B | 70 | 115/208-230 | None | 22.2 | 14.69 | |
| | 1740 | 184TC | 131539☆ | 685 | B | 81 | 230 | None | 21.0 | 14.69 | |

Motors in this column have NEMA Service Factors - see page 161 for details.

- ☆ Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.
- ♣ These totally enclosed single phase motors have 1.15 Service Factors.
- These motors are totally enclosed, non-ventilated—Others are fan cooled.
- † Class F insulated.
- Shaft extension has keyway and flat 180° apart for ease of mounting.
Useable shaft is 1 1/2" long by 1/2" diameter, 1/8" keyway.

TEFC • C FACE LESS BASE • SINGLE PHASE

| NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | Over- load Prot. | F.L. Amps 230V | "C" Dim. (Inches) | |
|---------------|-------------------|---------------|---------------|------------------------|-------------|------------------------|----------------------|-------------------------|-------|
| 48CZ➤ | 102661 | \$189 | A | 14 | 115/208-230 | None | 1.7 | 9.43 | |
| 48CZ➤ | 101765 | 216 | A | 18 | 115/208-230 | None | 2.7 | 9.19 | |
| | 56C | 110405♣ | 216 | A | 22 | 115/208-230 | None | 2.4 | 9.94 |
| | 56C | 114639 | 216 | A | 18 | 115/208-230 | None | 2.6 | 10.81 |
| 56C | 114175 | 186 | A | 20 | 115/208-230 | None | 3.2 | 10.31 | |
| | 56C | 110407● | 186 | A | 24 | 115/208-230 | None | 2.1 | 10.44 |
| 48CZ➤ | 102663 | 223 | A | 19 | 115/208-230 | None | 3.1 | 10.43 | |
| | S56C | 101766 | 232 | A | 22 | 115/208-230 | None | 3.3 | 9.94 |
| | 56C | 110076♣ | 233 | A | 23 | 115/208-230 | None | 2.9 | 9.94 |
| | 56C | 110038♣ | 245 | A | 25 | 115/208-230 | Man. | 2.9 | 9.94 |
| 56C | 110349♣ | 210 | A | 22 | 115/208-230 | None | 3.8 | 10.81 | |
| | 56C | 110409♣ | 224 | A | 25 | 115/208-230 | Man. | 3.8 | 10.81 |
| 48CZ➤ | 102665 | 260 | A | 22 | 115/208-230 | None | 4.0 | 10.44 | |
| | 56C | 110056♣ | 270 | A | 21 | 115/208-230 | None | 4.4 | 10.81 |
| | 56C | 110039♣ | 285 | A | 22 | 115/208-230 | Man. | 4.4 | 10.81 |
| | 56C | 114476 | 282 | A | 24 | 115/208-230 | Auto. | 4.4 | 10.81 |
| | 56C | 110411 | 471 | A | 37 | 115/208-230 | None | 4.9 | 12.81 |
| | 56C | 110413 | 243 | A | 26 | 115/208-230 | None | 5.0 | 11.31 |
| 56C | | 110412 | 253 | A | 28 | 115/208-230 | Man. | 5.0 | 11.31 |
| 56C | 110057♣ | 319 | A | 25 | 115/208-230 | None | 5.4 | 11.31 | |
| | 56C | 110040♣ | 334 | A | 26 | 115/208-230 | Man. | 5.4 | 11.31 |
| | 56C | 110308♣ | 331 | A | 28 | 115/208-230 | Auto. | 5.4 | 11.31 |
| | 56C | 110414☆ | 530 | A | 42 | 115/208-230 | None | 5.3 | 13.31 |
| 56C | 110416♣ | 285 | A | 28 | 115/208-230 | None | 6.0 | 11.81 | |
| | 56C | 110415 | 312 | A | 28 | 115/208-230 | Man. | 6.0 | 11.81 |
| 56C | 110058♣ | 366 | A | 33 | 115/208-230 | None | 6.4 | 11.81 | |
| | 56C | 110041♣ | 382 | A | 29 | 115/208-230 | Man. | 6.4 | 11.81 |
| | 143TC | 121001 | 415 | B | 32 | 115/208-230 | None | 6.4 | 12.25 |
| 56C | 110419 | 368 | A | 31 | 115/208-230 | None | 8.5 | 12.31 | |
| | 56C | 110418 | 384 | A | 31 | 115/208-230 | Man. | 8.5 | 12.31 |
| | 143TC | 120101 | 415 | B | 36 | 115/208-230 | None | 8.5 | 12.75 |
| 56C | 110420☆ | 413 | A | 37 | 115/208-230 | None | 8.6 | 12.81 | |
| | 56C | 110042☆ | 430 | A | 40 | 115/208-230 | Man. | 8.6 | 12.81 |
| | 145TC | 120017☆ | 469 | B | 40 | 115/208-230 | None | 8.6 | 13.75 |
| 56C | 110422♣ | 468 | A | 40 | 115/208-230 | None | 10.0 | 13.31 | |
| | 56C | 110421♣† | 485 | A | 41 | 115/208-230 | Man. | 10.0 | 13.31 |
| | 145TC | 120102♣† | 486 | B | 43 | 115/208-230 | None | 10.0 | 13.75 |
| 56C | 112136☆ | 551 | A | 41 | 115/230 | None | 9.2 | 13.31 | |
| | 145TC | 120060☆ | 564 | B | 45 | 115/230 | Man. | 10.0 | 14.25 |
| | 182TC | 131516 | 724 | B | 64 | 115/208-230 | None | 12.4 | 14.47 |
| ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 145TC | 120824☆ | 542 | B | 56 | 230 | Man. | 14.0 | 13.88 | |
| 184TC | 131545 | 852 | B | 82 | 115/208-230 | None | 16.8 | 16.47 | |
| 184TC | 131778☆ | 856 | B | 81 | 115/208-230 | None | 19.8 | 16.97 | |
| 184TC | 131540☆ | 888 | B | 104 | 230 | None | 23.0 | 17.47 | |

Motors in this column have NEMA Service Factors except as noted by ♣, which have 1.15 Service Factors.

C FACE MOTORS • SINGLE PHASE

WITH BASE • CAPACITOR START • GENERAL PURPOSE



C Face Motors



DRIP-PROOF • C FACE WITH BASE • SINGLE PHASE

| HP | RPM 60 Hz | NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | Over- load Prot. | F.L. Amps 230V | "C" Dim. (Inches) |
|-------|-----------------|---------------|-------------------|---------------|---------------|------------------------|-------------|------------------------|----------------------|-------------------------|
| 1/4 | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1/3 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1/2 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | S56C | 101651 | \$268 | A | 21 | 115/208-230 | None | 4.4 | 9.99 |
| 3/4 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | S56C | 101650 | 309 | A | 27 | 115/208-230 | None | 5.4 | 10.99 |
| 1 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 56C | 113930 | 354 | A | 34 | 115/208-230 | None | 6.4 | 10.88 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1 1/2 | 3450 | 56C | 114214☆ | 341 | A | 35 | 115/208-230 | Man. | 6.7 | 11.38 |
| | 1725 | 56HC | 113932☆□ | 381 | A | 39 | 115/208-230 | None | 8.6 | 11.84 |
| | 1725 | 56HC | 113700☆□ | 451 | A | 38 | 115/208-230 | Man. | 7.2 | 11.84 |
| 2 | 3450 | 56C | 114215☆ | 433 | A | 35 | 115/208-230 | Man. | 8.6 | 11.38 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 56HC | 113281☆□ | 468 | A | 45 | 115/208-230 | Man. | 8.6 | 12.88 |
| | 1725 | 145TC | 120992 | 409 | B | 45 | 115/230 | None | 10.5 | 13.28 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 3 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1740 | 184TC | 131629 | 559 | B | 70 | 115/208-230 | Man. | 16.9 | 14.19 |
| 5 | 3450 | 184TC | 131781☆ | 661 | B | 70 | 115/208-230 | None | 22.2 | 14.19 |
| | 1740 | 184TC | 131630☆ | 687 | B | 77 | 208-230 | Man. | 21.0 | 14.69 |
| 7 1/2 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 10 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1740 | ... | ... | ... | ... | ... | ... | ... | ... | ... |

Motors in this column have NEMA Service Factors - see page 161 for details.

TEFC • C FACE WITH BASE • SINGLE PHASE

| NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | Over- load Prot. | F.L. Amps 230V | "C" Dim. (Inches) |
|---------------|-------------------|---------------|---------------|------------------------|-------------|------------------------|----------------------|-------------------------|
| 56C | 114143 | \$222 | A | 22 | 115/208-230 | None | 2.6 | 10.81 |
| 56C | 114145 | 220 | A | 22 | 115/208-230 | None | 3.2 | 10.81 |
| 56C | 114144 | 235 | A | 24 | 115/208-230 | None | 3.2 | 10.81 |
| 56C | 110900●❖ | 235 | A | 25 | 115/208-230 | None | 2.9 | 9.94 |
| 56C | 110310 | 221 | A | 25 | 115/208-230 | None | 3.6 | 10.81 |
| 56C | 110734❖ | 284 | A | 22 | 115/208-230 | None | 4.4 | 10.81 |
| 56C | 112135 | 249 | A | 26 | 115/208-230 | None | 5.0 | 11.31 |
| 56C | 110905❖ | 340 | A | 26 | 115/208-230 | None | 5.4 | 11.31 |
| 56C | 110180 | 287 | A | 28 | 115/208-230 | None | 6.0 | 11.81 |
| 56C | 115877 | 287 | A | 28 | 115/208-230 | Man. | 6.0 | 11.81 |
| 56C | 110908❖ | 383 | A | 30 | 115/208-230 | None | 6.4 | 11.81 |
| 56C | 115879 | 383 | A | 32 | 115/208-230 | Man. | 6.4 | 11.81 |
| 56C | 110909 | 372 | A | 34 | 115/208-230 | None | 8.5 | 12.31 |
| 56HC | 110910☆❖□ | 455 | A | 39 | 115/208-230 | None | 8.6 | 12.81 |
| ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 56HC | 113931❖□† | 488 | A | 46 | 115/208-230 | None | 10.0 | 13.31 |
| 56C | 115878❖† | 488 | A | 43 | 115/208-230 | Man. | 10.0 | 13.31 |
| 145TC | 121008❖† | 488 | B | 43 | 115/208-230 | None | 10.0 | 13.75 |
| ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 145TC | 120274☆ | 615 | B | 49 | 115/230 | None | 9.2 | 14.25 |
| 145TC | 121465 | 615 | A | 44 | 115/208-230 | Man. | 9.2 | 13.75 |
| 145TC | 121060☆ | 548 | B | 51 | 230 | Man. | 14.0 | 13.88 |
| 184TC | 131631 | 854 | B | 84 | 115/208-230 | Man. | 16.8 | 16.47 |
| 184TC | 131632❖❖ | 859 | B | 103 | 230 | Man. | 19.8 | 16.97 |
| 184TC | 131633☆ | 895 | B | 86 | 230 | Man. | 23.0 | 16.97 |
| 213TC | 140694†☆ | 1008 | B | 120 | 208-230 | None | 32.0 | 19.07 |
| 215TC | 140695†☆ | 1204 | B | 138 | 208-230 | None | 41.5 | 20.57 |
| 215TC | 140678†☆ | 1165 | B | 152 | 230 | None | 40.0 | 20.71 |

Motors in this column have NEMA Service Factors except as denoted by ❖, which have 1.15 Service Factors.

- ☆ Capacitor start/capacitor run design for reduced amperage, others are capacitor start/induction run.
- ❖ These totally enclosed single phase motors have 1.15 Service Factors.
- These motors are totally enclosed, non-ventilated—Others are fan cooled.
- Combination 56H base motors have mounting holes for NEMA 56 and NEMA 143-145T and standard NEMA 56C face and shaft.
- † Class F insulated.

QUICK REFERENCE

| | |
|-------------------------------|---------|
| WASHGUARD® C FACE MOTORS..... | Page 28 |
| BRAKEMOTORS..... | 36 |
| WATTSAVER® C FACE MOTORS..... | 17 |



C FACE MOTORS • THREE PHASE

LESS BASE • GENERAL PURPOSE



DRIP-PROOF • C FACE LESS BASE • THREE PHASE

| HP | RPM 60 Hz | NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL. Amps 230V | % FL. Eff. | "C" Dim. (Inches) |
|-------|-----------------|---------------|-------------------|---------------|---------------|------------------------|-------------|---------------------|------------------|-------------------------|
| 1/6 | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1/4 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1/3 | 3450 | S56C | 100375 | \$170 | A | 15 | 208-230/460 | 1.7 | 68.0 | 9.31 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | S56C | 100048 | 187 | A | 17 | 208-230/460 | 1.6 | 64.3 | 9.49 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1/2 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | S56C | 100056 | 183 | A | 17 | 208-230/460 | 2.4 | 69.0 | 9.31 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | S56C | 100049 | 215 | A | 21 | 208-230/460 | 2.0 | 68.0 | 9.99 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | 56C | 110434 | 320 | A | 26 | 208-230/460 | 2.8 | 66.0 | 10.38 |
| 3/4 | 3450 | S56C | 100378 | 217 | A | 20 | 208-230/460 | 2.8 | 79.0 | 9.81 |
| | 1725 | S56C | 100050 | 240 | A | 24 | 208-230/460 | 2.8 | 75.0 | 10.49 |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | 143TC | 120063 | 345 | B | 36 | 208-230/460 | 3.4 | 75.5 | 11.28 |
| 1 | 3450 | 56C | 110111 | 249 | A | 22 | 208-230/460 | 3.6 | 80.6 | 9.88 |
| | 1725 | 56C | 110043 | 261 | A | 22 | 208-230/460 | 4.2 | 78.5 | 10.38 |
| | 1725 | 143TC | 120172 | 261 | B | 26 | 208-230/460 | 4.2 | 78.5 | 11.28 |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | 145TC | 120082 | 371 | B | 34 | 208-230/460 | 4.0 | 77.0 | 11.78 |
| 1 1/2 | 3450 | 56C | 110437 | 289 | A | 27 | 208-230/460 | 4.2 | 82.1 | 11.28 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 56C | 110044 | 305 | A | 27 | 208-230/460 | 5.6 | 78.5 | 10.88 |
| | 1725 | 145TC | 120081 | 287 | B | 34 | 208-230/460 | 5.6 | 78.5 | 11.78 |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 2 | 3450 | 56C | 113894 | 334 | A | 31 | 208-230/460 | 6.2 | 82.9 | 11.38 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 56C | 115553 | 326 | A | 32 | 208-230/460 | 6.2 | 78.5 | 11.19 |
| | 1725 | 145TC | 120035 | 316 | B | 33 | 208-230/460 | 6.2 | 78.5 | 12.28 |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |

TEFC • C FACE LESS BASE • THREE PHASE

| NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL. Amps 230V | % FL. Eff. | "C" Dim. (Inches) |
|---------------|-------------------|---------------|---------------|------------------------|-------------|---------------------|------------------|-------------------------|
| 48CZ | 102662 | \$175 | A | 15 | 208-230/460 | .94 | 64.0 | 9.43 |
| 48CZ | 101965 | 228 | A | 15 | 208-230/460 | 1.1 | 67.0 | 9.03 |
| 48CZ | 101966 | 199 | A | 18 | 208-230/460 | 1.0 | 78.0 | 9.31 |
| 48CZ | 101981 | 199 | A | 17 | 208-230/460 | 1.4 | 58.0 | 8.94 |
| S56C | 101648 | 194 | A | 17 | 208-230/460 | 1.0 | 78.0 | 9.56 |
| S56C | 101767 | 194 | A | 19 | 208-230/460 | 1.4 | 58.0 | 9.69 |
| 56C | 110446 | 192 | A | 20 | 208-230/460 | 1.0 | 68.0 | 9.94 |
| 48CZ | 102664 | 203 | A | 20 | 208-230/460 | 1.6 | 64.3 | 9.19 |
| S56C | 101769 | 211 | A | 20 | 208-230/460 | 1.6 | 64.3 | 9.69 |
| 56C | 110045 | 216 | A | 19 | 208-230/460 | 1.3 | 72.0 | 9.94 |
| 48C | 101291 | 328 | A | 20 | 208-230/460 | 1.8 | 73.0 | 9.31 |
| 56C | 113311 | 328 | A | 22 | 208-230/460 | 1.6 | 65.0 | 10.81 |
| 48C | 100449 | 223 | A | 23 | 208-230/460 | 1.6 | 67.0 | 10.06 |
| 56C | 110144 | 223 | A | 25 | 208-230/460 | 1.5 | 76.0 | 10.44 |
| 56C | 114176 | 223 | A | 19 | 208-230/460 | 2.6 | 75.0 | 10.31 |
| 48CZ | 100486 | 256 | A | 24 | 208-230/460 | 1.9 | 75.0 | 11.02 |
| 48CZ | 102666 | 245 | A | 24 | 208-230/460 | 2.0 | 73.0 | 9.69 |
| 56C | 110046 | 256 | A | 23 | 208-230/460 | 1.8 | 78.5 | 10.44 |
| 56C | 110458 | 247 | A | 19 | 208-230/460 | 2.0 | 74.0 | 10.81 |
| 56C | 110163 | 354 | A | 25 | 208-230/460 | 2.4 | 70.0 | 11.31 |
| 56C | 110448 | 234 | A | 21 | 208-230/460 | 2.4 | 75.5 | 10.81 |
| 56C | 110047 | 265 | A | 22 | 208-230/460 | 2.8 | 77.0 | 10.81 |
| 56C | 112378 | 370 | A | 29 | 208-230/460 | 3.0 | 75.5 | 11.81 |
| 143TC | 120097 | 370 | B | 33 | 208-230/460 | 3.0 | 75.5 | 12.25 |
| 56C | 110112 | 276 | A | 21 | 208-230/460 | 3.2 | 77.1 | 10.81 |
| 56C | 110048 | 283 | A | 24 | 208-230/460 | 3.8 | 77.0 | 11.31 |
| 143TC | 120024 | 283 | B | 26 | 208-230/460 | 3.8 | 77.0 | 11.75 |
| 56C | 112379 | 363 | A | 32 | 208-230/460 | 4.0 | 77.0 | 12.31 |
| 145TC | 120098 | 363 | B | 36 | 208-230/460 | 4.0 | 77.0 | 12.75 |
| 56C | 110192 | 304 | A | 28 | 208-230/460 | 4.2 | 80.3 | 11.81 |
| 143TC | 120105 | 300 | B | 33 | 208-230/460 | 4.2 | 80.3 | 12.75 |
| 56C | 110125 | 299 | A | 29 | 208-230/460 | 5.0 | 78.5 | 11.81 |
| 145TC | 120037 | 291 | B | 32 | 208-230/460 | 5.0 | 80.0 | 12.75 |
| 56C | 113634 | 414 | A | 39 | 208-230/460 | 5.7 | 77.0 | 13.31 |
| 145TC | 120161 | 414 | B | 39 | 208-230/460 | 5.7 | 77.0 | 13.75 |
| 56C | 111273 | 345 | A | 36 | 208-230/460 | 5.6 | 78.8 | 12.31 |
| 145TC | 120061 | 345 | B | 34 | 208-230/460 | 5.6 | 78.8 | 12.75 |
| 56C | 110451 | 320 | A | 34 | 208-230/460 | 6.2 | 81.5 | 12.81 |
| 145TC | 120038 | 311 | B | 35 | 208-230/460 | 6.2 | 81.5 | 12.75 |
| 184TC | 131525 | 474 | B | 59 | 208-230/460 | 7.4 | 80.0 | 13.97 |

► Shaft extension has keyway and flat 180° apart for ease of mounting.

Useable shaft is 1 1/2" long by 1/2" diameter, 1/8" keyway.

● These motors are totally enclosed, non-ventilated—Others are fan cooled.

CONTINUED ON NEXT PAGE

C FACE MOTORS • THREE PHASE

LESS BASE • GENERAL PURPOSE



C Face Motors



DRIP PROOF • C FACE LESS BASE • THREE PHASE

| HP | RPM 60 Hz | NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL. Amps 230V | % FL. Eff. | "C" Dim. (Inches) | |
|------|-----------------|---------------|-------------------|---------------|---------------|------------------------|-------------|---------------------|------------------|-------------------------|-------|
| 3 | 3450 | 56C | 114420 | \$357 | A | 37 | 208-230/460 | 8.0 | 80.0 | 11.88 | |
| | 3450 | 145TC | 121187 | 301 | B | 39 | 208-230/460 | 8.0 | 80.0 | 12.28 | |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1725 | 145TC | 121405 | 377 | B | 45 | 208-230/460 | 8.6 | 82.5 | 13.12 | |
| | 1740 | 182TC | 131489 | 345 | B | 43 | 208-230/460 | 8.0 | 80.0 | 11.69 | |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 5 | 3450 | 182TC | 131779 | 368 | B | 84 | 208-230/460 | 13.2 | 82.5 | 13.19 |
| | | 1725 | 184TC | 131490 | 379 | B | 55 | 208-230/460 | 14.2 | 84.0 | 12.69 |
| | | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 7½ | 3450 | 184TC | 131780 | 487 | B | 92 | 208-230/460 | 18.4 | 84.0 | 14.19 | |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1740 | 184TC | 131739 | 536 | B | 108 | 230/460 | 20.0 | 87.0 | 14.70 | |
| | 1740 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1750 | S213TC | 131527 | 536 | B | 88 | 230/460 | 20.0 | 87.0 | 15.69 | |
| | 1760 | 213TC | 140580 | 536 | B | 115 | 208-230/460 | 20.0 | 88.5 | 15.25 | |
| 10 | 3450 | 213TC | 140688 | 660 | B | 85 | 208-230/460 | 25.0 | 85.5 | 16.53 | |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1740 | 215TC | 140108† | 675 | B | 132 | 208-230/460 | 28.0 | 89.5 | 16.75 | |
| 1750 | ... | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 15 | 3450 | 215TC | 140689 | 897 | B | 100 | 208-230/460 | 38.0 | 86.5 | 18.03 | |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| | 1760 | ... | ... | ... | ... | ... | ... | ... | ... | ... | |
| 20 | 3500 | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 1760 | ... | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 25 | 1760 | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 30 | 1760 | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 40 | 1770 | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 50 | 1770 | ... | ... | ... | ... | ... | ... | ... | ... | | |
| 60 | 1770 | ... | ... | ... | ... | ... | ... | ... | ... | | |

TEFC • C FACE LESS BASE • THREE PHASE

| NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL. Amps 230V | % FL. Eff. | "C" Dim. (Inches) |
|---------------|-------------------|---------------|---------------|------------------------|-------------|---------------------|------------------|-------------------------|
| 56C | 111630♣ | \$393 | A | 37 | 208-230/460 | 8.0 | 80.0 | 12.81 |
| 145TC | 120993♣ | 393 | B | 38 | 208-230/460 | 8.0 | 80.0 | 13.25 |
| 182TC | 131513 | 433 | B | 55 | 208-230/460 | 8.0 | 84.0 | 13.97 |
| 56C | 113890♣ | 425 | A | 43 | 208-230/460 | 8.6 | 82.5 | 13.81 |
| 145TC | 121035♣ | 413 | B | 44 | 208-230/460 | 8.6 | 82.5 | 14.25 |
| 182TC | 131491 | 388 | B | 52 | 208-230/460 | 9.0 | 82.5 | 13.97 |
| S213TC | 131642 | 598 | B | 89 | 208-230/460 | 9.6 | 81.5 | 16.96 |
| 184TC | 131514 | 485 | B | 68 | 208-230/460 | 12.4 | 85.5 | 13.97 |
| 184TC | 131492 | 444 | B | 64 | 208-230/460 | 13.2 | 82.5 | 14.48 |
| 215TC | 140535 | 809 | B | 120 | 208-230/460 | 17.6 | 87.5 | 18.21 |
| 184TC | 131510 | 581 | B | 89 | 208-230/460 | 18.4 | 86.5 | 14.97 |
| 213TC | 131912 | 603 | B | 91 | 208-230/460 | 18.4 | 86.5 | 15.46 |
| 213TC | 151345 | 613 | C | 158 | 208-230/460 | 18.4 | 85.5 | 18.84 |
| 184TC | 131606 | 572 | B | 66 | 208-230/460 | 19.6 | 87.0 | 16.47 |
| 213TC | 151346 | 591 | C | 162 | 208-230/460 | 18.4 | 87.9 | 18.84 |
| S213TC | 131528 | 572 | B | 102 | 208-230/460 | 19.6 | 87.0 | 16.96 |
| ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 215TC | 140690 | 715 | B | 105 | 208-230/460 | 24.0 | 86.5 | 20.57 |
| 215TC | 151347 | 723 | C | 172 | 208-230/460 | 23.8 | 86.2 | 20.34 |
| 215TC | 140109† | 686 | B | 141 | 208-230/460 | 26.0 | 89.5 | 18.71 |
| 215TC | 151348 | 697 | C | 185 | 208-230/460 | 24.6 | 88.4 | 20.34 |
| 215TC | 140691 | 1009 | B | 145 | 208-230/460 | 37.0 | 88.5 | 20.57 |
| 215TC | 151349 | 1016 | C | 200 | 208-230/460 | 36.0 | 89.2 | 16.61 |
| 254TC | 151350 | 989 | C | 284 | 208-230/460 | 37.0 | 90.0 | 23.80 |
| 256TC | 151351 | 1307 | C | 270 | 208-230/460 | 48.0 | 89.6 | 25.50 |
| 256TC | 151352 | 1249 | C | 367 | 208-230/460 | 48.0 | 91.2 | 25.50 |
| 284TC | 151507 | 1573 | C | 390 | 208-230/460 | 60.0 | 91.3 | 26.26 |
| 286TC | 151508 | 1891 | C | 411 | 208-230/460 | 70.0 | 91.5 | 27.83 |
| 324TC | 151509 | 2420 | C | 548 | 208-230/460 | 92.0 | 92.1 | 29.53 |
| 326TC | 151510 | 2791 | C | 594 | 208-230/460 | 114.2 | 92.4 | 31.02 |
| 364TC | 151519 | 4194 | C | 778 | 208-230/460 | 140.0 | 92.7 | 32.64 |

† Class F insulated.
♣ These totally enclosed three phase motors have 1.0 service factors.

SHADED FRAME INDICATES CAST IRON CONSTRUCTION



C FACE MOTORS • THREE PHASE

WITH BASE • GENERAL PURPOSE



DRIP PROOF • C FACE WITH BASE • THREE PHASE

| HP | RPM 60 Hz | NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL Amps 230V | % FL Eff. | "C" Dim. (Inches) |
|-------|-----------------|---------------|-------------------|---------------|---------------|------------------------|-------------|--------------------|-----------------|-------------------------|
| 1/3 | 1725 | S56C | 100599 | \$207 | A | 18 | 208-230/460 | 1.6 | 64.3 | 9.49 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1/2 | 3450 | S56C | 100600 | 197 | A | 17 | 208-230/460 | 2.4 | 69.0 | 9.31 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | S56C | 100601 | 235 | A | 20 | 208-230/460 | 2.0 | 68.0 | 9.99 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 3/4 | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | S56C | 100602 | 260 | A | 25 | 208-230/460 | 2.8 | 75.0 | 10.49 |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1 | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 56C | 110901 | 306 | A | 28 | 208-230/460 | 4.2 | 78.5 | 10.38 |
| | 1740 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 1 1/2 | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 56C | 110902 | 322 | A | 29 | 208-230/460 | 5.6 | 78.5 | 10.88 |
| | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 2 | 1125 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | 56C | 114218 | 377 | A | 34 | 208-230/460 | 6.2 | 82.9 | 11.38 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 3 | 1725 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1725 | 145TC | G120275 | 344 | B | 35 | 208-230/460 | 6.0 | 84.0 | 13.78 |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 3 1/2 | 3500 | 145TC | G121072 | 345 | B | 35 | 230/460 | 7.2 | 84.0 | 12.78 |
| | 3515 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3510 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1740 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 5 | 1740 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1760 | 182TC | G130325 | 390 | B | 58 | 208-230/460 | 8.4 | 86.5 | 12.69 |
| | 1750 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1140 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 7 1/2 | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3450 | 184TC | G131250 | 606 | B | 92 | 208-230/460 | 17.6 | 87.5 | 14.70 |
| | 3450 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3510 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 10 | 1740 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1760 | 213TC | G150170 | 511 | C | 157 | 208-230/460 | 19.6 | 88.5 | 16.38 |
| | 1170 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |

TEFC • C FACE WITH BASE • THREE PHASE

| NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL Amps 230V | % FL Eff. | "C" Dim. (Inches) |
|---------------|-------------------|---------------|---------------|------------------------|-------------|--------------------|-----------------|-------------------------|
| 56C | 110911 ● | \$232 | A | 18 | 208-230/460 | 1.3 | 72.0 | 9.94 |
| 56C | 114141 | 231 | A | 19 | 208-230/460 | 1.3 | 70.0 | 10.81 |
| 56C | 110182 ● | 227 | A | 26 | 208-230/460 | 1.5 | 76.0 | 10.44 |
| 56C | 114142 | 227 | A | 21 | 208-230/460 | 2.6 | 67.0 | 10.81 |
| 56C | 110913 ● | 268 | A | 22 | 208-230/460 | 1.8 | 78.5 | 10.44 |
| 56C | 114140 | 268 | A | 19 | 208-230/460 | 2.0 | 74.0 | 10.81 |
| 56C | 110914 | 357 | A | 25 | 208-230/460 | 2.4 | 70.0 | 11.31 |
| 56C | 110915 | 246 | A | 23 | 208-230/460 | 2.8 | 75.5 | 10.81 |
| 56C | 110916 | 285 | A | 22 | 208-230/460 | 2.8 | 77.0 | 10.81 |
| 56C | 116340 | 372 | A | 29 | 208-230/460 | 3.0 | 75.5 | 11.81 |
| 143TC | 120485 | 372 | B | 34 | 208-230/460 | 3.0 | 75.5 | 13.25 |
| 56C | 110181 | 291 | A | 24 | 208-230/460 | 3.6 | 77.1 | 10.81 |
| 56C | 110912 | 304 | A | 24 | 208-230/460 | 3.6 | 77.0 | 11.31 |
| 145TC | G121286 | 339 | B | 35 | 208-230/460 | 3.8 | 82.5 | 13.25 |
| 145TC | G120428 | 411 | B | 35 | 208-230/460 | 3.6 | 80.0 | 13.25 |
| 56C | 110917 | 326 | A | 29 | 208-230/460 | 4.8 | 80.3 | 11.81 |
| 143TC | G121290 | 355 | B | 27 | 208-230/460 | 4.0 | 82.5 | 13.25 |
| 56C | 110918 | 321 | A | 30 | 208-230/460 | 5.0 | 78.5 | 11.81 |
| 145TC | G121287 | 338 | B | 37 | 208-230/460 | 4.4 | 84.0 | 13.25 |
| 56HC | 114198 □ | 430 | A | 41 | 208-230/460 | 5.7 | 77.0 | 13.31 |
| 56HCZ | 121288 * | 430 | B | 44 | 208-230/460 | 5.7 | 77.0 | 13.75 |
| 56C | 113927 | 369 | A | 34 | 208-230/460 | 5.6 | 78.8 | 12.31 |
| 145TC | G121510 | 390 | B | 45 | 208-230/460 | 5.0 | 84.0 | 13.75 |
| 56HC | 116106 □ | 342 | A | 36 | 208-230/460 | 6.2 | 81.5 | 12.81 |
| 145TC | G120276 | 354 | B | 45 | 208-230/460 | 6.0 | 84.0 | 14.25 |
| 184TC | G131497 | 516 | B | 76 | 208-230/460 | 7.2 | 86.5 | 15.47 |
| 56HC | 114615 □ | 412 | A | 38 | 208-230/460 | 8.0 | 80.0 | 12.81 |
| 145TC | G120991 | 443 | B | 35 | 208-230/460 | 7.4 | 85.5 | 13.75 |
| 182TC | G131899 | 487 | B | 61 | 208-230/460 | 7.6 | 85.5 | 13.97 |
| 182TC | G151564 | 495 | C | 94 | 208-230/460 | 8.5 | 87.5 | 16.76 |
| 56HC | 116107 □ | 433 | B | 45 | 208-230/460 | 8.6 | 82.5 | 13.81 |
| 56HCZ | 116388 * | 433 | A | 46 | 208-230/460 | 8.6 | 82.5 | 14.25 |
| 182TC | G130326 | 436 | B | 68 | 208-230/460 | 8.2 | 87.5 | 13.96 |
| 182TC | G151565 | 484 | C | 94 | 208-230/460 | 8.5 | 87.5 | 16.14 |
| 215TC | G140602 | 646 | B | 118 | 230/460 | 12.0 | 87.5 | 17.71 |
| 184TC | G131173 | 483 | B | 80 | 208-230/460 | 12.0 | 87.5 | 14.47 |
| 184TC | G151446 | 516 | C | 101 | 208-230/460 | 12.0 | 87.5 | 18.71 |
| 184TC | G130328 | 501 | B | 81 | 208-230/460 | 13.0 | 87.5 | 14.97 |
| 184TC | G151566 | 532 | C | 101 | 208-230/460 | 13.8 | 87.5 | 16.14 |
| 215TC | G140482 | 831 | B | 144 | 208-230/460 | 17.6 | 87.5 | 18.21 |
| 184TC | G130990 | 625 | B | 91 | 208-230/460 | 16.8 | 88.5 | 15.97 |
| S213TC | G131774 | 635 | B | 70 | 208-230/460 | 16.8 | 88.5 | 16.96 |
| 213TC | G150166 | 650 | C | 153 | 208-230/460 | 17.8 | 88.5 | 18.95 |
| 213TC | G140183 | 600 | B | 153 | 208-230/460 | 20.4 | 89.5 | 17.71 |
| 213TC | G150165 | 606 | C | 156 | 208-230/460 | 19.2 | 89.5 | 18.95 |
| 254TC | G150138 | 1202 | C | 221 | 208-230/460 | 20.0 | 89.5 | 23.80 |

† Class F insulated. □ Combination 56H base motors have mounting holes for NEMA 56 and NEMA 143-145T and standard NEMA 56C face and shaft.
 ● These motors are totally enclosed, non-ventilated—Others are fan cooled. * 56HCZ motors have mounting holes for NEMA 56 and NEMA 143-5T and a standard NEMA 143-5T shaft.
 † These totally enclosed three phase motors have 1.0 service factors.

Catalog numbers in blue are NEW items.
SHADED FRAME INDICATES CAST IRON CONSTRUCTION
Catalog numbers in green are EPACT motors.

C FACE MOTORS • THREE PHASE

WITH BASE • GENERAL PURPOSE



DRIP PROOF • C FACE WITH BASE • THREE PHASE

| HP | RPM 60 Hz | NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL Amps 230V | % FL Eff. | "C" Dim. (Inches) |
|----|-----------------|---------------|-------------------|---------------|---------------|------------------------|-------------|--------------------|-----------------|-------------------------|
| 10 | 3450 | 213TC | G140692 | \$673 | B | 105 | 208-230/460 | 23.4 | 88.5 | 18.03 |
| | 3510 | 213TC | G150171 | 677 | C | 180 | 208-230/460 | 27.6 | 88.5 | 16.38 |
| | 1740 | 215TC | G140146 | 662 | B | 162 | 208-230/460 | 28.0 | 89.5 | 16.75 |
| | 1760 | 215TC | G150172 | 672 | C | 183 | 208-230/460 | 25.0 | 89.5 | 18.62 |
| | 1170 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 15 | 3450 | 215TC | G140693 | 931 | B | 130 | 208-230/460 | 34.0 | 90.2 | 19.28 |
| | 3510 | 215TC | G150173 | 936 | C | 191 | 208-230/460 | 35.0 | 89.5 | 18.62 |
| | 1770 | 254TC | G150175 | 960 | C | 266 | 208-230/460 | 37.6 | 91.0 | 21.32 |
| | 1170 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | ... | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 20 | 3525 | 254TC | G150070 | 1133 | C | 275 | 208-230/460 | 46.6 | 90.2 | 21.38 |
| | 1770 | 256TC | G150071 | 1169 | C | 325 | 208-230/460 | 49.0 | 91.0 | 23.03 |
| 25 | 3550 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3550 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1770 | 284TC | G150073 | 1456 | C | 390 | 208-230/460 | 59.6 | 91.7 | 23.54 |
| 30 | 3550 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 3550 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1770 | 286TC | G151377 | 1668 | C | 430 | 208-230/460 | 72.0 | 92.4 | 25.00 |
| 40 | 3550 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1780 | 324TC | G151378 | 2114 | C | 491 | 208-230/460 | 96.0 | 91.0 | 26.02 |
| 50 | 3550 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1780 | 326TC | G151379 | 2503 | C | 599 | 208-230/460 | 120.0 | 93.0 | 27.52 |
| 60 | 3570 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1780 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 75 | 3570 | ... | ... | ... | ... | ... | ... | ... | ... | ... |
| | 1780 | ... | ... | ... | ... | ... | ... | ... | ... | ... |

Motors in this column have NEMA Service Factors — see page 161 for details.

TEFC • C FACE WITH BASE • THREE PHASE

| NEMA Frame | Catalog Number | List Price | Disc. Sym. | App. Wgt. (lbs.) | Voltage | FL Amps 230V | % FL Eff. | "C" Dim. (Inches) |
|---------------|-------------------|---------------|---------------|------------------------|-------------|--------------------|-----------------|-------------------------|
| 213TC | G140696 | \$750 | B | 115 | 208-230/460 | 24.0 | 89.5 | 20.57 |
| 215TC | G150168 | 762 | B | 163 | 208-230/460 | 23.6 | 89.5 | 20.36 |
| 215TC | G140147 | 701 | B | 162 | 208-230/460 | 26.0 | 89.5 | 18.71 |
| 215TC | G150167 | 714 | C | 178 | 208-230/460 | 25.2 | 89.5 | 20.36 |
| 256TC | G150139 | 1340 | C | 252 | 208-230/460 | 26.2 | 89.5 | 25.50 |
| 215TC | G140697 | 1045 | B | 161 | 208-230/460 | 36.0 | 90.2 | 20.57 |
| ... | ... | ... | ... | ... | ... | ... | ... | ... |
| 254TC | G150103 | 1063 | C | 245 | 208-230/460 | 35.0 | 90.2 | 23.80 |
| 254TC | G150102 | 1024 | C | 258 | 208-230/460 | 36.6 | 91.0 | 23.80 |
| 284TC | G150104 | 1995 | C | 369 | 208-230/460 | 40.4 | 90.2 | 26.26 |
| 256TC | G150079 | 1343 | C | 257 | 208-230/460 | 46.2 | 90.2 | 25.50 |
| 256TC | G150080 | 1249 | C | 275 | 208-230/460 | 48.2 | 91.0 | 25.50 |
| 284TSC | G150106 | 1586 | C | 362 | 208-230/460 | 58.2 | 91.0 | 24.88 |
| 284TC | G151383 | 1586 | C | 362 | 208-230/460 | 58.2 | 91.0 | 26.26 |
| 284TC | G150081 | 1610 | C | 387 | 208-230/460 | 58.8 | 92.4 | 26.26 |
| 286TSC | G150108 | 1872 | C | 375 | 208-230/460 | 69.2 | 91.0 | 26.46 |
| 286TC | G151396 | 1872 | C | 375 | 208-230/460 | 69.2 | 91.0 | 27.83 |
| 286TC | G150082 | 1903 | C | 433 | 208-230/460 | 69.8 | 92.4 | 27.83 |
| 324TSC | G150110 | 2759 | C | 574 | 208-230/460 | 93.0 | 91.7 | 28.00 |
| 324TC | G150083 | 2430 | C | 572 | 208-230/460 | 95.2 | 93.0 | 29.53 |
| 326TSC | G150112 | 2838 | C | 604 | 208-230/460 | 112.0 | 92.4 | 29.53 |
| 326TC | G150084 | 2816 | C | 631 | 208-230/460 | 117.8 | 93.0 | 31.02 |
| 364TSC | G150114 | 4642 | C | 860 | 208-230/460 | 139.0 | 93.0 | 30.51 |
| 364TC | G150085 | 4248 | C | 699 | 208-230/460 | 138.0 | 93.6 | 32.64 |
| 365TSC | G150115 | 5573 | C | 773 | 208-230/460 | 172.0 | 93.0 | 31.49 |
| 365TC | G150086 | 5389 | C | 757 | 208-230/460 | 173.0 | 94.1 | 33.62 |

Motors in this column have 1.15 Service Factors, except noted by ♣ which have a 1.00 Service Factor.

SHADED FRAME INDICATES CAST IRON CONSTRUCTION

Catalog numbers in green are EPACT motors.