



LeCentric™ Interchange Kits & Accessories

**Gear+Motor™ Dimensions (Inches)**

Series	A	AB		B	BA	C			D	E	F	H	OA	P		U +0.000/ -0.000	V	OUTPUT KEY
		56C/140TC	180TC			2-Stage	3-Stage	56C/140TC						180TC				
		56/140	180			56/140	56/140	56/140TC						180TC				
717	5.71	5.31	6.38	5.51	2.28	8.83	NA	9.60	2.95	4.33	4.33	0.35	6.12	6.59	8.47	0.750	1.57	3/16 x 1.12
727	5.71	5.31	6.38	6.02	2.95	9.23	NA	10.00	3.54	4.33	5.12	0.35	6.71	6.59	8.47	1.000	1.97	1/4 x 1.62
747	6.69	5.31	6.38	7.76	3.54	11.49	12.02	11.83	4.53	5.31	6.50	0.55	8.52	6.59	8.47	1.250	2.36	1/4 x 2.00
757	6.69	5.31	6.38	7.76	3.54	12.20	12.73	12.47	4.53	5.31	6.50	0.55	8.58	6.59	8.47	1.250*	2.36	1/4 x 2.00

Refer to page 173 for motor length dimensions.

\* 1.375" diameter shaft is available. Contact LEESON for availability.

**Motor Mounting Position**

Conduit box position viewed from input side of reducer.

