

# C FACE MOTORS • THREE PHASE

LESS BASE • GENERAL PURPOSE



## DRIP-PROOF • C FACE LESS BASE • THREE PHASE

HP	RPM 60 Hz	NEMA Frame	Catalog Number	App. Wgt. (lbs.)	Voltage	FL. Amps 230V	% FL. Eff.	"C" Dim. (Inches)
1/4	1725	...	...	...	...	...	...	...
	1725	...	...	...	...	...	...	...
1/3	1725	S56C	<b>100048</b>	17	208-230/460	1.6	64.3	9.49
	1725	...	...	...	...	...	...	...
1/2	1725	S56C	<b>100049</b>	21	208-230/460	2.0	68.0	9.99
	1725	...	...	...	...	...	...	...
3/4	1725	S56C	<b>100050</b>	24	208-230/460	2.8	75.0	10.49
1	1725	56C	<b>110043</b>	22	208-230/460	4.2	78.5	10.38
	1725	143TC	<b>120172</b>	26	208-230/460	4.2	78.5	11.28
1½	1725	56C	<b>110044</b>	27	208-230/460	5.6	78.5	10.88
	1725	145TC	<b>120081</b>	34	208-230/460	5.6	78.5	11.78
2	1725	56C	<b>115553</b>	32	208-230/460	6.2	78.5	11.19
	1725	145TC	<b>120035</b>	33	208-230/460	6.2	78.5	12.28
3	1725	...	...	...	...	...	...	...
	1725	145TC	<b>121405</b>	45	208-230/460	8.6	82.5	13.12
	1740	182TC	<b>131489</b>	43	230/460	8.0	80.0	11.69
5	1725	184TC	<b>131490</b>	55	208-230/460	14.2	84.0	12.69
7½	1740	184TC	<b>131739</b>	108	230/460	20.0	87.0	14.70

## TEFC • C FACE LESS BASE • THREE PHASE

NEMA Frame	Catalog Number	App. Wgt. (lbs.)	Voltage	FL. Amps 230V	% FL. Eff.	"C" Dim. (Inches)
S56C	<b>101648</b> ●	17	208-230/460	1.0	78.0	9.56
S56C	<b>101767</b>	19	208-230/460	1.4	58.0	9.69
S56C	<b>101769</b>	20	208-230/460	1.6	64.3	9.69
S56C	<b>102863</b> ●	19	208-230/460	1.3	77.0	9.56
S56C	<b>102861</b> ●	23	208-230/460	1.8	77.0	10.06
S56C	<b>102860</b>	19	208-230/460	2.0	73.0	10.19
56C	<b>110047</b>	22	208-230/460	2.8	77.0	10.81
56C	<b>110048</b>	24	208-230/460	3.8	77.0	11.31
143TC	<b>120024</b>	26	208-230/460	3.8	77.0	11.75
56C	<b>110125</b>	29	208-230/460	5.0	78.5	11.81
145TC	<b>120037</b>	32	208-230/460	5.0	80.0	12.75
56C	<b>110451</b>	34	208-230/460	6.2	81.5	12.81
145TC	<b>120038</b>	35	208-230/460	6.2	81.5	12.75
56C	<b>113890</b> †	43	208-230/460	8.6	82.5	13.81
145TC	<b>121035</b> †	44	230/460	8.6	82.5	14.25
182TC	<b>131491</b>	52	230/460	9.0	82.5	13.97
184TC	<b>131492</b>	64	230/460	13.2	82.5	14.48
184TC	<b>131606</b>	66	208-230/460	19.6	87.0	16.47

● These motors are totally enclosed, non-ventilated—Others are fan cooled.  
 † Class F insulated.  
 † These totally enclosed three phase motors have 1.0 service factors.

SHADED FRAME INDICATES CAST IRON CONSTRUCTION